



Weight	1.25 kg
Type of construction	FW runner block
Mechanical format	KWD Ball runner block
Size	35
Design	SNS Flanged, normal, standard height
Format	CS Carbon steel
Preload class	C1 low preload
Accuracy class	N Normal
Seal	SS Standard seal
Ball retainer	0 Without ball retainer
Lubrication	01 Prelubricated, preserved
Bearing grease	S1 Dynalub 510
Fitting	M8X13

10 MILLION METER RELUBRICATION SCHEDULE

<u>RATINGS</u>		<u>ENGLISH</u>	
51,800 N	Basic Dynamic Capacity	11,645	lbs
80,900 N	Static Capacity	18,187	lbs
1,110 Nm	Roll Moment Dynamic Capacity	819	ft-lbs
1,740 Nm	Roll Moment Static Capacity	1,283	ft-lbs
7,620 Nm	Pitch/Yaw Moment Dynamic Capacity	5620	ft-lbs
1,130 Nm	Pitch/Yaw Moment Static Capacity	833	ft-lbs

Bosch Rexroth BSHP Ball Rail Runner Block
 KWD-035-SNS-CS-C1-N-SS-0-01-S1-00-BX-LS-000-RS-000-01
PN: 1622-314-20

MorrellGroup
 Evolution in Controls

www.morrell-group.com

rexroth
 A Bosch Company

UNITS : mm