



4 PLCS Mounting Hole
M8 Tap 12mm Deep



Weight	0.85 kg
Type of construction	FW runner block
Mechanical format	KWD Ball runner block
Size	30
Design	SNS Flanged, normal, standard height
Format	CS Carbon steel
Preload class	C1 low preload
Accuracy class	N Normal
Seal	SS Standard seal
Ball retainer	0 Without ball retainer
Lubrication	01 Prelubricated, preserved
Bearing grease	S1 Dynalub 510
Fitting	M8X12

10 MILLION METER RELUBRICATION SCHEDULE

<u>RATINGS</u>	<u>ENGLISH</u>
36,500 N Basic Dynamic Capacity	8,205 lbs
48,100 N Static Capacity	10,813 lbs
630 Nm Roll Moment Dynamic Capacity	465 ft-lbs
830 Nm Roll Moment Static Capacity	612 ft-lbs
440 Nm Pitch/Yaw Moment Dynamic Capacity	325 ft-lbs
580 Nm Pitch/Yaw Moment Static Capacity	428 ft-lbs

Bosch Rexroth BSHP Ball Rail Runner Block
KWD-030-SNS-CS-C1-N-SS-0-01-S1-00-BX-LS-000-RS-000-01
PN: 1622-714-20

MorrellGroup
Evolution in Controls

www.morrell-group.com

rexroth
A Bosch Company

UNITS : mm