



4 PLCS Mounting Hole
 Either M12 Tap Or Can Be Used as
 Thru Hole for M10 Nut and Bolt

2 PLCS Mounting Hole
 Either M12 Tap



Weight
 Type of construction
 Mechanical format
 Size
 Design
 Format
 Preload class
 Accuracy class
 Seal
 Ball retainer
 Lubrication
 Bearing grease
 Fitting

3.00 kg
 FW runner block
 KWD Ball runner block
 45
 FNS Flanged, normal, standard height
 CS Carbon steel
 C0 without preload
 N Normal
 SS Standard seal
 0 Without ball retainer
 01 Prelubricated, preserved
 S1 Dynalub 510
 M6X8

10 MILLION METER RELUBRICATION SCHEDULE

RATINGS		ENGLISH	
86,400 N	Basic Dynamic Capacity	19,425	lbs
132,000 N	Static Capacity	29,675	lbs
2,330 Nm	Roll Moment Dynamic Capacity	1,715	ft-lbs
3,560 Nm	Roll Moment Static Capacity	2,625	ft-lbs
1,540 Nm	Pitch/Yaw Moment Dynamic Capacity	1,136	ft-lbs
2,350 Nm	Pitch/Yaw Moment Static Capacity	1,733	ft-lbs

Bosch Rexroth BSHP Ball Rail Runner Block
 KWD-045-FNS-CS-C0-N-SS-0-01-S1-00-BX-LS-000-RS-000-01
PN: 1651-494-20

MorrellGroup
 Evolution in Controls

www.morrell-group.com

rexroth
 A Bosch Company

UNITS : mm