



**Low Drag Runner Block Version**  
**No End Seals – Oil Preserved**



Weight	3.00 kg
Type of construction	FW runner block
Mechanical format	KWD Ball runner block
Size	45
Design	FNS Flanged, normal, standard height
Format	CS Carbon steel
Preload class	C0 – 10 micron clearance
Accuracy class	N Normal
Seal	LS/99 – Low Friction/No seal
Ball retainer	0 Without ball retainer
Lubrication	02 Preserved
Bearing grease	00 No Lube
Fitting	M12X15

**10 MILLION METER RELUBRICATION SCHEDULE**

<u>RATINGS</u>	<u>ENGLISH</u>
86,400 N Basic Dynamic Capacity	19,425 lbs
132,000 N Static Capacity	29,675 lbs
2,330 Nm Roll Moment Dynamic Capacity	1,715 ft-lbs
3,560 Nm Roll Moment Static Capacity	2,625 ft-lbs
1,540 Nm Pitch/Yaw Moment Dynamic Capacity	1,136 ft-lbs
2,350 Nm Pitch/Yaw Moment Static Capacity	1,733 ft-lbs

Bosch Rexroth BSHP Ball Rail Runner Block  
 KWD-035-SNS-CS-C0-N-LS/99-0-02-00-BX-LS-000-RS-000-01  
**PN: 1651-494-25\_R030101331\_LD** **Low Drag**

 <b>MorrellGroup</b> Evolution in Controls <a href="http://www.morrell-group.com">www.morrell-group.com</a>	 <b>rexroth</b> A Bosch Company
<b>UNITS : mm</b>	